




BI-5 高低壓組合泵(含變量葉片泵)

Combination Pumps (With variable displacement vane pumps)

VD1+SL, VE1+SL



選購指南 HOW TO ORDER

VD1	-30	F	A2	+SL
系列編號 SERIES NUMBER VD1 VE1	排量 DISPLACEMENT (cc/rev) 參照性能表 REFER TO SPECIFICATION	裝配形式 MOUNTING TYPE F: 法蘭型 FLANGE MOUNTING TYPE L: 腳座型 FOOT MOUNTING TYPE	壓力調整範圍 PRESSURE ADJUSTING RANGE A1:8~20kgf/cm ² A2:15~35kgf/cm ² A3:30~70kgf/cm ²	結合泵型號 COMBINE PUMP MODEL NO. KIP,PA

性能表 SPECIFICATION

型號 MODEL		最高壓力 MAX PRESSURE kgf/cm ²	無負荷流量(l/min) FLOW OF UNLOADING		壓力調整範圍 PRESSURE ADJUSTING RANGE (kgf/cm ²)	轉速(rpm) INPUT SPEED		重量 WEIGHT	
腳座型 FOOT TYPE	法蘭型 FLANGE TYPE		1500rpm	1800rpm		最高 MAX.	最低 MIN.	腳座型 FOOT TYPE	法蘭型 FLANGE TYPE
VD1-30LA*+SL	VD1-30FA*+SL	70+210	25+SL	30+SL	A1:8-20 A2:15-35 A3:30-70	1800	800	14	11
VE1-40LA*+SL	VE1-40FA*+SL	70+210	33.3+SL	40+SL				14	11


※注：1、本系列泵與所需之齒輪泵配合使用，但訂購時，齒輪泵價格另計。
2.SL、為結合泵之型號規格請寫全。

REMARK: 1.The series pumps must be used together with gear pump, price we offer is fixed displacement vane pump only, the gear pump with another price.
SL: Model of combined pump please give us detail model when place order.

BI-6 變量葉片泵(出口法蘭型)

Variable Displacement Vane Pumps (With Flange Outlet Type)

VFA1, VFB1, VFD1, VFE1



選購指南 HOW TO ORDER

VFA1	-12	F	A2
系列編號 SERIES NUMBER VFA1 VFB1 VFD1 VFE1	排量 DISPLACEMENT (cc/rev) 參照性能表 REFER TO SPECIFICATION	裝配形式 MOUNTING TYPE F: 法蘭型 FLANGE MOUNTING TYPE	壓力調整範圍 PRESSURE ADJUSTING RANGE A1:8~18kgf/cm ² A2:15~35kgf/cm ² A3:30~55kgf/cm ² A4:50~70kgf/cm ²

性能表 SPECIFICATION

型號 MODEL	最高壓力 MAX. PRESSURE kgf/cm ²	無負荷流量(l/min) FLOW OF UNLOADING		壓力調整範圍 PRESSURE ADJUSTING RANGE (kgf/cm ²)	轉速(rpm) INPUT SPEED		配管尺寸 PORTS SIZE			重量 WEIGHT (kg)
		1500rpm	1800rpm		最高 MAX.	最低 MIN.	出口 OUT	入口 IN	泄油 DR.	
VFA1-12F-A*	70	10	12	A1:8-18 A2:15-35 A3:30-55 A4:50-70	1800	800	3/8"	1/2"	1/4"	6.1
VFA1-15F-A*		12.5	15							
VFB1-20F-A*		16.7	20							
VFD1-25F-A*		21	25				1/2"	3/4"	8.7	
VFD1-30F-A*		25	30							
VFE1-40F-A*	33.3	40								