




BII- 1 定量葉片泵

Fixed Displacement Vane Pumps

50T, 150T



選購指南 HOW TO ORDER

50T	-36	-F	R
系列編號 SERIES NUMBER 50T 150T	排量 DISPLACEMENT (cc/rev) 參照性能表 REFER TO SPECIFICATION	裝配形式 MOUNTING TYPE F: 法蘭型 FLANGE MOUNTING TYPE L: 腳座型 FOOT MOUNTING TYPE	旋轉方向 SHAFT ROTATING (VIEW FROM SHAFT END) R: 順時針方向 CLOCKWISE L: 逆時針方向 COUNTER- CLOCKWISE

※50T軸心 Shaft F: $\phi 19.05$ L: $\phi 22$, 150T軸心 Shaft $\phi 30.0$

性能表 SPECIFICATION


型號 MODEL	吐出容積 cc/rev				最高使用壓力 MAX PRESSURE kgf/cm ²	容許轉速rpm PORTS SIZE		配管尺寸 PORTS SIZE		重量 WEIGHT		
	回轉速度 r. p. m					最高 MAX.	最低 MIN.	出口 OUT	入口 IN	腳座型 FOOT TYPE	法蘭型 FLANGE TYPE	
	1000	1200	1500	1800								
50T-07	-	8.2	10.3	12.5	70	1200	1800	3/4"	1"	10.5	9.0	
50T-12	12.2	14.3	18.2	21.5		950	1800	3/4"	1"	10.5	9.0	
50T-14	14.5	17.3	21.5	26.0		950	1800	3/4"	1"	10.5	9.0	
50T-17	17.1	20.0	25.5	31.5		950	1800	3/4"	1"	10.5	9.0	
50T-20	20.0	23.8	29.8	36.1		950	1800	3/4"	1"	10.5	9.0	
50T-23	23.1	27.4	34.3	41.5		950	1800	3/4"	1"	10.5	9.0	
50T-26	26.0	31.2	39.2	46.8		950	1800	3/4"	1"	10.5	9.0	
50T-30	30.2	36.2	45.2	54.1		950	1800	3/4"	1"	10.5	9.0	
50T-36	36.2	41.5	54.5	64.2		950	1800	3/4"	1"	10.5	9.0	
50T-39	39.0	45.6	58.3	70.0		950	1800	3/4"	1"	10.5	9.0	
50T-43	43	51.6	-	-		950	1200	3/4"	1"	26	9.0	
150T-48	48.2	58.0	72.6	86.8		70	900	1800	1 1/4"	1 1/2"	26	25
150T-61	61.4	73.8	92.0	110.6			900	1800	1 1/4"	1 1/2"	26	25
150T-75	75.0	90.5	112.5	135.6			900	1800	1 1/4"	1 1/2"	26	25
150T-94	94.0	112.8	141.3	169.5	900		1800	1 1/4"	1 1/2"	26	25	
150T-116	116.2	139.5	-	-	900		1200	1 1/4"	1 1/2"	26	25	
150T-125	125.2	150.2	-	-	900		1200	1 1/4"	1 1/2"	26	25	

另可提供雙聯型式，詳細請洽康百世·朝田技術部

BII- 2 雙聯訂量葉片泵(低壓型)

Fixed Displacement Double Pumps

50T+50T、150T+50T、
150T+150T系列



選購指南 HOW TO ORDER

150T+50T	-48	+07	-L	R
系列號碼 SERIES NUMBER 雙聯葉片泵 (低壓型) DOUBLE VANE PUMP (LOW)	大泵排量 BIG PUMP DISPLACEMENT 參照規格表150T ACCORDING TO THE SPECIFICATIONS IN TABLE 150T	小泵排量 SMALL PUMP DISPLACEMENT 參照規格表50T ACCORDING TO THE SPECIFICATIONS IN TABLE 50T	安裝型式 MOUNTING TYPE F: 法蘭式 L: 腳座式 F: FLANGE MOUNTING TYPE L: FOOT MOUNTING TYPE	旋轉方向(從軸端看) DIRECTION OF ROTATION (VIEWED FROM SHAFT END) R: 順時針方向 L: 逆時針方向 R: CLOCKWISE L: COUNTER CLOCKWISE

性能表 SPECIFICATION

型號 MODEL	最高使用壓力 MAX PRESSURE kgf/cm ²	排量 ml/rev DISPLACEMENT		轉速r/min SPEEDr/min		重量 WEIGHT	
		大排量泵 BIG PUMP DISPLACEMENT	小排量泵 SMALL PUMP DISPLACEMENT	最低 MIN.	最高 MAX.	法蘭型 FLANGE TYPE	腳座型 FOOT TYPE
50T+50T	7	同 50T Same as 50T	同 50T Same as 50T	900	1500	18	21
150T+50T		同 150T Same as 150T	同 50T Same as 50T			34	35.5
150T+150T		同 150T Same as 150T	同 150T Same as 150T			47	48.5

注：近軸側為前泵，一般較大流量。 Note: the proximal side for the pump, and generally larger flow.