





C-3 定量齒輪泵

Quantitative Gear Pump

K1P、SGP1A、PLS系列



選購指南 HOW TO ORDER

K1P	-3	R	-	F	-V	210
系列號碼 SERIES NUMBER K1P	規格代號 1.2.3.4 6.7.9.10	旋轉方向(從軸端看) DIRECTION OF ROTATION (VIEWED FROM SHAFT END)	軸型式 SHAFT TYPE	安裝型式 MOUNTING TYPE	溢流閥 RELIEF VALVE	溢流閥設定壓力 210kgf/cm <sup>2</sup> RELIEF VALVE PRESSURE SETTING 210kgf/cm <sup>2</sup>
SGP1A, PLS 定量齒輪泵 GEAR METERING PUMP	參照規格表 REFERENCE SPECIFICATION	R: 順時針方向 R: CLOCKWISE L: 逆時針方向 L: COUNTER-CLOCKWISE	無記號 —: 平鍵軸 (標準型) NO MARK: KEY SHAFT (STANDARD)	F: 法蘭型 F: FLANGE TYPE L: 腳座型 L: FOOT TYPE	無記號: 不附溢流閥 V: 附溢流閥 NO MARK: NOT ATTACHED RELIEF VALVE V: WITH AN RELIEF VALVE	無“V”標記 時省略 WITHOUT THE “V” MARKING OMIT

性能表 SPECIFICATION

型號 MODEL	排量 ml/rev DISPLACEMENT	最高壓力 (MPa) MAXIMUM PRESSURE	額定壓力 (MPa) RATED PRESSURE	容許轉速(rpm) SPEED RANGE		配管尺寸 PORTS SIZE				重量kg WEIGHT							
				最低 MIN.	最高 MAX.	入口 IN		出口 OUT									
						L型	F型	L型	F型								
K1P1	1.0	24.5	20.6	1300	6000	Ø 17.5	PT1/2"	Ø 14.8	PT1/2"	1.58							
K1P2	2.0			900						1.63							
K1P3	3.0			850						1.65							
K1P4	4.0			800						5000	1.67						
K1P6	6.0			700						4000	1.69						
K1P7	7.5			600						3500	1.71						
K1P9	9.0			550						3000	1.73						
K1P10	10.5			500						2500	1.75						
SGP1A16	16.2			24.5						20.6	500	4000	Ø 25	PT1"	Ø 19	PT3/4"	3.3
SGP1A18	18.3										500						3.4
SGP1A20	20.4	500	3.5														
SGP1A23	23.7	400	3500		Ø 24	PT1 1/2"	Ø 24	PT1"	3.7								
SGP1A25	24.9								4.0								
SGP1A27	27.8								4.0								
SGP1A30	29.9								4.1								
SGP1A32	33.2	20.6	18.6		3000	Ø 30	Ø 24	PT1"	4.2								
SGP1A34	34.1								4.3								
SGP1A36	36.6								17.2		4.5						
PLS3035	37.2			24.5					21.0	500	3000	Ø 24	PT1 1/2"	Ø 19	PT1"	15.02	
PLS3045	47.5	500	17.52														
PLS3050	52.2	500	3000		17.52												
PLS3060	63.3	500	2500		18.02												

※備注: 1、本產品目前僅供應順時針轉向之定量齒輪泵, 設計時請注意。  
 ※Remark: This product is currently only supply a clockwise gear pump, please note when you design.