




BII-7 雙聯定量葉片泵 (高壓型)

Fixed Displacement Double Vane Pumps
PV2R12、PV2R13系列



選購指南 HOW TO ORDER

PV2R12	-59	+12	-F	R	-R	R	X
系列號碼 SERIES NUMBER	大泵排量 BIG PUMP DISPLACEMENT	小泵排量 SMALL PUMP DISPLACEMENT	裝配形式 MOUNTING TYPE	旋轉方向 (從軸端看) DIRECTION OF ROTATING (VIEWED FROM SHAFT END)	吸油口方向 IN POSITION	大泵出口方向(從軸端看) LARGE PUMP OUTLET DIRECTION (VIEWED FROM SHAFT END)	小泵出口方向(從軸端看) SMALL PUMP OUTLET DIRECTION (VIEWED FROM SHAFT END)
雙聯定量葉片泵(高壓型) DOUBLE FIXED DISPLACEMENT VANE PUMP (PRESSURE TYPE)	參照規格表 REFER TO SPECIFICATION	參照規格表 REFER TO SPECIFICATION	F: 法蘭型 FLANGE MOUNTING TYPE L: 腳座型 FOOT MOUNTING TYPE	R: 順時針方向 (標準) CLOCKWISE (STANDARD) L: 逆時針方向 COUNTER CLOCKWISE	無標記: 向上(標準) UNMARKED: UP (STANDARD) D: 向下 D: DOWN R: 向右 R: RIGHT L: 向左 L: LEFT	無標記: 向上(標準) UNMARKED: UP (STANDARD) D: 向下 D: DOWN R: 向右 R: RIGHT L: 向左 L: LEFT	無標記: 左上45° (標準) UNMARKED: UP LEFT 45 DEGREES(STANDARD) X: 右上45° X: UP RIGHT 45 DEGREES Y: 右下45° Y: DOWN RIGHT 45 DEGREES Z: 左下45° Z: DOWN LEFT 45 DEGREES

性能表 SPECIFICATION

型號 MODEL	最高使用壓力MPa MAX.PRESSURE		大泵排量 m ³ /rev BIG PUMP DISPLACEMENT	小泵排量 m ³ /rev SMALL PUMP DISPLACEMENT	轉速範圍(rpm) SPEED RANGE		配管尺寸(PT) THE PIPING SIZES			重量Kg WEIGHT	
	最高 MAX.	額定 RATED			最低 MIN.	最高 MAX.	入口 IN	出口(小) OUT(SMALL)	出口(大) OUT(BIG)	腳座型 FOOT TYPE	法蘭型 FLANGE TYPE
PV2R12	21 *17.5	17.5 *16	41,47, 53,59, 65	6,8,10 12,14, 17,19, 23,25, *31	950	1800	2"	1/2"	3/4"	30	25
PV2R13			76,94, 116				3"	1/2"	1 1/4"		

備注: 雙聯泵轉速需視個別泵而定, 大排量泵建議使用低轉速(如1200rpm以下), 以減低噪音。

Remark: Double pump, the r.p.m depending on the individual pump.
Big displacement pump is recommended to use Low-speed (under 1200 rpm) to reduce noise.