



BII-9 定量葉片泵 (低噪音高壓改良型)

Fixed Displacement Vane pump (low noise high pressure modified)  
SVQ25、35、45系列



選購指南 HOW TO ORDER

SVQ 25	-26	-F	R	L	R
系列號碼 SERIES NUMBER 定量葉片泵 (低噪音高壓改良型) VANE PUMP (LOW NOISE HIGH PRESSURE IMPROVED TYPE)	排量 DISPLACEMENT (cc/rev) 參照規格表 REFER TO SPECIFICATION	裝配形式 MOUNTING TYPE F: 法蘭型 FLANGE MOUNTING TYPE L: 腳座型 FOOT MOUNTING TYPE	旋轉方向(從軸端看) DIRECTION OF ROTATION (VIEWED FROM SHAFT END) R: 順時針方向 L: 逆時針方向 R: CLOCKWISE (STANDARD) L: COUNTER CLOCKWISE	出油口方向 OUT POSITION U: 向上 D: 向下 R: 向右 L: 向左(標準) U: UP D: DOWN R: RIGHT L: LEFT(STANDARD)	進油口方向 IN POSITION U: 向上 D: 向下 R: 向右(標準) L: 向左 U: UP D: DOWN R: RIGHT(STANDARD) L: LEFT

性能表 SPECIFICATION

型號 MODEL	最高使用壓力 (額定壓力)MPa MAX.PRESSURE	排量 ml/rev UNLOADING DISPLACEMENT	容許轉速r/min PERMISSIBLE SPEED		重量Kg WEIGHT	
			最低 MIN.	最高 MAX.	法蘭型 FLANGE TYPE	腳座型 FOOT TYPE
SVQ25-18	21.0(17.5)	18	600	1800	17	19
SVQ25-22		22				
SVQ25-26		26.2				
SVQ25-32		32.1				
SVQ25-38		38.2				
SVQ25-43		43.2				
SVQ25-52		52.3				
SVQ25-60	21.0(17.5)	60.2	600	1500	34	42
SVQ25-65		65.3		1200		
SVQ25-75		75				
SVQ35-60	21.0(17.5)	60.3	600	1800	34	42
SVQ35-66		66.4				
SVQ35-76		76.3				
SVQ35-82		82.3				
SVQ35-88		88.3				
SVQ35-94		94.5				
SVQ35-108		108.2				
SVQ35-116	17.5(16)	116.1	600	1500	52	60
SVQ35-125		124.6		1200		
SVQ45-136		136				
SVQ45-156	17.5(16)	156	600	1500	52	60
SVQ45-189		189		1200		
SVQ45-216		216				
SVQ45-237		237				

備注: 為降低噪音, 高排量泵建議使用較低轉速(如1200rpm) Note: to reduce noise, high displacement pump recommended the use of low speed (such as 1200rpm)