




C-4 潤骨泵、潤滑電機泵組

Lubricate Pump, Motor & Pump Assembly

VOP



選購指南 HOW TO ORDER

| VOP | -206 | -F | +RV | -A2 |
|------------------------------|--|---|--|--|
| 系列號碼 SERIES NUMBER VOP | 排量 DISPLACEMENT (cc/rev) 參照性能表 REFER TO SPECIFICATION | 安裝形式 MOUNTING TYPE F: 法蘭型 FLANGE MOUNTING TYPE | 調整閥 RELIEF VALVE RV: 附調整閥 RV: WITH ADJUST PRESSURE VALVE —: 無調整閥 —: WITHOUT ADJUST PRESSURE VALVE | 壓力調整範圍 PRESSURE ADJ. RANGE A1: 8-18kgf/cm ² A2: 5-20kgf/cm ² A3: 15-30kgf/cm ² |

性能表 SPECIFICATION

| 型號 MODEL | 最高使用壓力 MAX. PRESSURE kgf/cm ² | 無負荷時之流量(d/min) DELIVERY AT UNLOADING | | 壓力調整範圍 PRESSURE ADJUSTING RANGE kgf/cm ² | 容許轉速(rpm) SPEED RANGE | | 配管尺寸 PT PORTS SIZE | | 重量kg WEIGHT |
|-------------|---|---|---------|--|--------------------------|------------|-----------------------|----------|----------------|
| | | 1500rpm | 1800rpm | | 最高 MAX. | 最低 MIN. | 出口 OUT | 入口 IN | |
| VOP-203 | 25 | 4.5 | 5.4 | A1:3~8 A2:5~20 A3:15~30 | 1800 | 800 | 1/2" | 1/2" | 3.7 |
| VOP-204 | | 6.0 | 7.2 | | | | | | |
| VOP-206 | | 9.0 | 10.8 | | | | | | |
| VOP-208 | | 12.0 | 14.4 | | | | | | |
| VOP-210 | | 15.0 | 18.0 | | | | | | |
| VOP-212 | 20 | 18.0 | 21.6 | 1500 | | 3/4" | 3/4" | 4.2 | |
| VOP-216 | | 24.0 | 28.8 | | | | | 4.3 | |
| VOP-220 | | 30.0 | 36.0 | | | | | 4.5 | |
| | 15 | | | | | | | 4.8 | |
| | | | | | | | | | 5.3 |

C-5 油壓專用電機

Electric Motors Special For Hydraulic Application

M



選購指南 HOW TO ORDER


| M | 3P | 4H | 523 | +SL |
|--------------------------|--|---|--|---|
| 系列號碼 SERIES NUMBER | 馬力數 HORSE POWER | 馬達形式 MOTOR TYPE | 使用電源 ELECTRIC POWER | 結合泵型號 COMBINE PUMP MODEL NUMBER |
| M | 1P: 1HP 2P: 2HP 3P: 3HP 5P: 5HP | V: 立式VERTICAL H: 臥式HORIZON S: 浸油式 SUBMERSED 極數 POLES 6: 6極 6POLES 4: 4極 4POLES | 523: 50HZ 220V-380V 524: 50HZ 220V-440V 623: 60HZ 220V-380V 624: 60HZ 220V-440V 512: 50HZ 110V-220V 612: 60HZ 110V-220V | 40L:VE1 30L:VD1 20L:VB1 KIP、PV2R1 SGP1A PV2R2 BS..... |

※詳細規格請洽康百世·朝田技術部
Detail Specification Please Contact Kompass Technical Department

C-6 電機泵組

Electric Motors Combined Pump Units

MP



選購指南 HOW TO ORDER

| MP | 3P | 4H | 523 | +SL |
|--------------------------|--|---|--|---|
| 系列號碼 SERIES NUMBER | 馬力數 HORSE POWER | 馬達形式 MOTOR TYPE | 使用電源 ELECTRIC POWER | 結合泵型號 COMBINE PUMP MODEL NUMBER |
| MP | 1P: 1HP 2P: 2HP 3P: 3HP 5P: 5HP | V: 立式VERTICAL H: 臥式HORIZON S: 浸油式 SUBMERSED 極數 POLES 6: 6極 6POLES 4: 4極 4POLES | 523: 50HZ 220V-380V 524: 50HZ 220V-440V 623: 60HZ 220V-380V 624: 60HZ 220V-440V 512: 50HZ 110V-220V 612: 60HZ 110V-220V | 40L:VE1 30L:VD1 20L:VB1 KIP、PV2R1 SGP1A PV2R2 BS..... |

※詳細規格請洽康百世·朝田技術部
Detail Specification Please Contact Kompass Technical Department