



K-5 數位式壓力計/壓力繼電器/壓力傳送器

Digital Type Pressure Gauges

DPG-75直立式、DPS-75直立式附法蘭、
DPS-75埋入式附法蘭



油壓記號
SYMBOL

特色:

- 精度全刻化1%
- 壓力範圍真空至1000kg/cm²(15,000psi)
- 正壓力單位:bar,psi,kg/cm²,MPa,以及kPa
- 負壓力單位:"Hg,cmHg,mmHg,以及bar
- 5 1/2位數字藍光背光LCD
- 最高壓力顯示
- CE認證
- ABS塑料烤漆外殼
- 自動歸零校正

配件:

- 壓力轉接頭
- 7/16 -20 SAE Oring接頭
- 3/8"或1/2"轉接頭
- (電話詢問有關其它轉接頭)

FEATURES

- ± 1% Full Scale Accuracy.
- Ranges from Vacuum to 15,000 PSIG (1,000 kg/cm²)
- Positive Pressures (bar, psi, kg/cm², MPa, and kPa)
- Negative Pressures ("Hg, cmHg, mmHg, bar).
- 5 1/2 Digits Blue Backlit LCD.
- High Pressure Capture.
- CE Compliant.
- Rugged ABS Plastic Housing with black lacquered
- Customer Recalibration.
- Zero Offset/Tare.

ACCESSORIES

- Pressure Adapters
- TO 7/16"-20 SAE Oring Connection.
- TO 3/8", 1/2" Connection Adapters.
- (Call factory for other fittings.)

選購指南 HOW TO ORDER

DPG	75	A120	(200)	N	L	N	B	1	1
-----	----	------	-------	---	---	---	---	---	---

或15
DPS/PT
才有
DPS才有

型號 Model

DPG = 數位式壓力計 DPG = Digital Pressure Gauge
DPS = 數位式壓力開關 DPS = Digital Pressure Switch
PT = 壓力傳送器 (只使用D24電源) PT = Pressure Transducer / Transmitter (using D24 power only)

電源 Power

D24 = 輸入 5-24 VDC 二芯電源線 D24 = 5-24 Volts DC Input (2-wire wiring/ 1.5 meters)
A120 = 100-120 VAC 變壓器 + D24 A120 = 100-120 Volts AC Adapter (included) + D24
A240 = 220-240 VAC 變壓器 + D24 A240 = 220-240 Volts AC Adapter (included) + D24

壓力範圍 (PSI) / 公斤 Pressure Ranges (PSI) / KG

V = 真空 V=Vacuum	0-280 = (280)/20	0-2800 = (2.8K)/200	0-15000 = (15K)/1000
0-15 = (15)/1	0-350 = (350)/25	0-3500 = (3.5K)/250	
0-30 = (30)/2	0-500 = (500)/35	0-4200 = (4.2K) /300	
0-40 = (40)/3	0-570 = (570)/40	0-5000 = (5.0K) /350	
0-60 = (60)/4	0-700 = (700)/50	0-5700 = (5.7K) /400	
0-100 = (100)/7	0-1000 = (1.0K)/70	0-7000 = (7.0K)/500	
0-140 = (140)/10	0-1400 = (1.4K)/100	0-8500 = (8.5K)/600	
0-200 = (200)/15	0-2100 = (2.1K)/150	0-10000 = (10K)/700	

壓力接頭 Type of Connection

N = NPT N = NPT
P = PT/BSP(T) P = PT/BSP(T)
B = BSP/PF B = BSP/PF

安裝方式 Type of Mounting

L = 直立式 L = Lower Mount
B = 埋入式 B = Lower Back Mount

法蘭 Flange

N = 不安裝 N = Without Front Flange
F = 安裝前法蘭 F = With Front Flange

壓力單位設定 Default Engineering Unit

B = bar P = psi K = kg/cm²
M = MPa A = kPa 1 = "Hg
2 = cmHg 3 = mmHg

輸出訊號 (PT 才有) Output Signal (PT Only)

1 = 4-20 mA 2 = 0-5 VDC 3 = 0-10 VDC

上限A(NO)接點 (DPS 才有) High Setting Points/Contacts (DPS Only)

0 = 無 1 = 1 接點 2 = 2 接點 3 = 3 接點 4 = 4 接點

下限B(NC)接點 (DPS 才有) Low Setting Points/Contacts (DPS Only)

0 = 無 1 = 1 接點 2 = 2 接點 3 = 3 接點 4 = 4 接點

接頭尺寸 Size of Connection

標準1/4" PT STANDARD 1/4"PT